

Survey of Section 24 T. 4 R. 2 *W*



FIELD NOTES.

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
A { sugar	8	S 63° W	22 1/2				
{ stone set							
B { no witness							
C { dogwood	6	S 9° E	3 1/2				
D { walnut	12	S 19° E	3 1/2				
{ ash	12	N 15° E	28				

Feb 13 1913 I met the following parties by agreement at the residence of Miner Shivelys namely J. L. Butcher Thomas Nelson with Elinger J. P. Turner and James Henry and proceeded to run the lines necessary to determine the boundary lines & corners of Thomas Nelsons land situated in the north west corner of the south east quarter section of 24 town / range 2 west and established the following corners as follows
the center corner of said said section by the witness trees
witness

b { Black walnut 12 in S 19° E 22 links
Ash 12 " N 15° E 24 "

and the south west corner is 40 rods south of center of section
witness

A { Sugar 8 in S 65° W 22 $\frac{1}{2}$ links

the south east corner is 80 rods east of the south west corner
stone set

b { no witness

the north east corner is 80 rods east of center of section
witness

c { dog wood 4 in S 9° E 3 $\frac{1}{2}$ links

by an agreement of the parties I had Herbert Hazel assistant surveyor and with Elinger and James Henry chairmen and myself as flag man

I hereby certify the foregoing to be a true and correct report of the survey made by me and verily believe

C. R. Whitaker
M. C. J.